



### DIRECTIONS

**Rnd 1 (RS):** Use Adjustable Ring Method to begin, ch 4 (counts as tr), working in center of ring 2 tr, dc, tr, dc, 2 tr, ch 3 (counts as tr), join rnd with sl st in ring. Pull gently on tail to tighten ring. Fasten off. Weave in the ends.

### ABBREVIATIONS

beg—begin(ning); ch—chain; dc—double crochet;  
hdc—half double crochet; rnd(s)—round(s); RS—right side;  
sc—single crochet; sl—slip; st(s)—stitch(es);  
tr—treble crochet

### FINISHED MEASUREMENTS

Approximately 1 3/4" [4.5 cm] wide x 1 1/2" [4 cm] tall

### MATERIALS

- **#4 medium weight yarn:** Approximately 2 yds [1.8 m]
- Boye® crochet hook size US H [5 mm]
- Yarn needle

### GAUGE

Gauge is not critical for this project.

### SPECIAL STITCHES

**Adjustable Ring Method:** Wrap yarn into a ring, ensuring that the tail falls behind the working yarn. Grip ring and tail firmly between middle finger and thumb. Insert hook through center of ring, yarn over with working yarn and pull up a loop. Chain the appropriate number and work stitches of first round in the ring. After the first round of stitches is worked, pull gently on tail to tighten ring.



EASY